

CMPP8318 Polyester Rollup Latex GB 200 - 8mil

Polyester Rollup Latex GB 200 is designed by 100% opaque Grey Back PET Film with poly resin coating in matte finish. Saturated and vivid output. With "opaque" and "layflat" quality, ideal for different portable display stand banner, POP/POS, poster, etc.

USEFUL INFORMATION

| Parameter | Test Method | Value |
|---------------------------|------------------|-------------------------|
| Support Material | DIN 60001 | 180um Gray Back Film |
| Caliper | DIN 53370 | 8mil |
| Denier | DIN EN ISO 2060 | - |
| Coating Type | | 20um Poly Resin Coating |
| Adhesive | | - |
| Adhesive Thickness | | - |
| Surface Material | | PET |
| Finish | DIN 53370 | Matte |
| Liner Type | | - |
| Whitenss | DIN 53354 | 93 +/- 1 |
| Opacity | DIN 53363 | 100% |
| Flame Resistance | NFPA 701 | - |
| Lo Temp (No Crack at ...) | ISO 13934-1:1999 | 5°C (41F) |
| Shelf Time | | 12 Months |

APPLICATION COMPATIBILITY

| Parameter | Range | Other Factors |
|----------------------|--|---------------|
| Typical Applications | Banners, Flags, POP Displays, Signs | |
| Outdoor Durability | Up to 6 Months Indoor, but largely dependent on environmental conditions, methods of installation, printing, and post-print finishing. | |
| Print Technology | Solvent, UV, Latex, Screen | |
| Standard Widths | 30", 36", 42", 54", 60" x 164 ft - custom widths x length available by special order | |

The information above is derived from internal testing by our company and based on information received from our suppliers. The values shown are for reference only, and are provided without guaranty and do not constitute a warranty, expressed or implied. The purchaser should determine, prior to use, the suitability of this material for his/her specific purpose. Data represents and average and is not intended for use as a specification.